

Mud Tank 245BBL /10,290GAL

SPECIFICATION

- Capacity: 245 BBL (10,290 gal)
- Height: 5'6" Width: 8'6" Length 41'8 ½ " (Tank Length) 45'9" (Overall nose to tail)
- · V-Shaped Floor for easy draining
- · Smooth Walls for easy cleaning
- Front Drain: 6" outlet port (weld neck flange, butterfly valve, threaded flange, male plug & chain)
- Rear Drain: 4" outlet port (weld neck flange, butterfly valve, threaded flange, male plug, chain & handle lock)
- Outlet Ports: (2) 4" outlet ports at front (weld neck flange, butterfly valve, threaded flange, male plug & chain)
- Manways: (1) 20" steel manway W/Buna-N gasket at passenger side near rear
- · Hook-up: Open front Hook-up
- Suspension: Spring 22.5 k capacity
- Tires: Conventional, 12 Plyes
- Wheels: 8.25 x 22.5
- Axle: 71.5 track, 22.500 lbs. capacity
- Ladder on Front
- · Vertical Tanks cylinder style tank
- Floor 448"x96"x3/8 Plate A36 Floor Main Floor Rails 12"x20.7" Structural Channel Floor Crossmembers ¼" A36 Plate

- Side ¼" Plate A36 / 6"x 2¾"x ¼" Formed Side Stakes
 - (1) 20" Steel Manway Located Passenger Side
- Front ¼" Plate A36 / 6" x 2¾" x ¼" Formed Horizontal Support
 - (2) Outlet Port 4" Weld Neck Flange \
 4" Butterfly Valve \ 4" Threaded Flange \
 4" Male Plug

3" DD X 17" II

- Rear ¼" Plate A36
 - (1) Drain Port 4" Weld Neck Flange \
 4" Butterfly Valve\4" Threaded
 Flange\4"Male Cross Plug
 - Suspension 3 Leaf Spring, 22,500lbs capacity Axle 71.5" Track, 22,500lbs Capacity Tires 11R22.5 12 PLYS Wheels 8.25x22.5 Steel
- Blast Interior Surface Preparation SSPC-SP-10 Near-White Metal Blast. Exterior Surface Preparation _SSPC-SP-6 Commercial Blast Cleaning
- Paint (Interior) Epoxy Phenolic 100% Solid 20.0

 -30.0 mils D.F.T. (Exterior) Primer Coat Epoxy
 3.0-4.0 mils D.F.T (Exterior) Finish Coat
 Polyurethane 3.0- 4.0 mils D.F.T
- Exterior top finish coat apply with grit for nonslip surface front ladder to be safety yellow
- Placard (2) 11 go Placard Driver & Passenger side (Customer Specifications)
- · Hydro Tested at 3 PSI



