

Mud Tank 91BBL / Roll Off

SPECIFICATION

Capacity: 3,822 Gal (91 BBL)

Length: 240" Tank Length/279" Overall Length

Width: 96" Tank Inside/102" Overall Width

Height: 39.5" Tank Height/48" Overall Height

Platform - Outside Roll Construction (36" Inside Rails)

(2) - 6"x15.63" Long Sill Rails/HD Nose Cones /1" Thick Open Hook

(2) - 6"x15.63" Outer Channel Floor Rails

3/8" Plate A36 Floor (Flat Bottom Floor

Configuration)

1/4" Plate A36 Formed Channel Floor Crossmembers (16" on Center)

1/4" Plate A36 Formed Channel Rub Rail (each side of tank)

8" Sch4 x 8" Long Rear Platform Rollers

4" O.D. x 6" Long Front Nose Rollers Sides - 1/4" Plate A36/6" x 23/4" x 1/4" Formed Side Stakes

Front - 1/4" Plate A36

(2) -Outlet Port -4" Weld Neck Flange \ 4" Buna -N Gasket\ 4" Blind Flange

(1) Drain Port -6" Weld Neck Flange \ 6" Buna-N Gasket\ 6" Blind Flange

Rear - ¼" Plate A36/(1) -¼" Formed Horizontal Support (1) -Drain Port -4" Weld Neck Flange \ 4" Buna N Gasket \4" Blind Flange

Unassembled Extras -

(2) 4" Butterfly valve assembles for front ports(1) 6" Butterfly valve assemble for front drain

(1) 4" Internal pipe for sump draining

All these items are included in tank but are to be delivered unassembled

23' DD X 17"

Blast -

Interior surface preparation - SSPC-SP-10 Near-

White Metal Blast

Exterior surface preparation - SSPC-SP-6

Commercial Blast Cleaning

(Interior) Epoxyphenolic 100% solid 20.0 - 30.0 Mils D.F.T.

(Exterior) Primer Coat Epoxy 3.0 -4.0 Mils D.F.T.

(Exterior) Finish Coat Polurethane 3.0 - 4.0 Mils D.F.T

Exterior Top Finish Coat: Apply with grit for non-slip

Front Ladder: To be safety yellow

Placard -

(2) 11 ga. Placard - Driver & Passenger side

(Customer Specifications)

Hydro -Tested at 3 PSI



