



## Mobile Service Unit Loading and Construction

### SPECIFICATION

#### Vehicle Summary:

- Peterbilt 388; C-15 Caterpillar Engine 475HP Diesel Fuel Type;
- Transmission FRO18210C 10 Spd; Engine Brake; Air Trac Suspension; 3.90
- Ratio; Aluminum Wheels; 274" Wheel Base; Tandem Axle; 40,000 lbs Rear
- Axle Weight; 14,600 lbs Front Axle Weight.

#### CARB Engine Idling Compliance:

- PACCAR PX-6, PX-8 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed sticker on the driver's door to identify them as meeting the NOx idling standard

#### Backhoe Summary

- Cat 420e; engine model-C4.4 ACERT DT; Gross power-101hp; Operating weight- 24,251lbs; shipping height-8.23'; 4 wheel drive; max backhoe digging depth-14.5'; max loading height-8.23'.

#### Trailer Summary

- Trail max TD-20\_D; GVWR-25,600lbs; length-20'; Tilt bed



#### NORTHERN CALIFORNIA

402 Hartz Avenue, Building C  
Danville, CA 94526  
p: 925-229-2900 | f: 925-553-2616

#### SOUTHERN CALIFORNIA

3272 Greyhawk Ct.  
Carlsbad, CA 92010  
p: 760-642-2712 | f: 707-317-0076