

36 Ft Steel End Dump (Auto Tarp)

MS DM BLUE SUPPORT RING

SPECIFICATION

- Manufacture Hanson
- Trailer will measure 36' from trailer kingpin to center of rear axle
- Inside dimension of trailer at top rail, 33' 7"
- Elliptical body style
- Body depth will be 38" (approximately 24 ½ yards at water level)
- Body constructed with 3/16" AR 450 HARDOX plate
- Front end nose plate made from 3/16" AR 450 HARDOX plate
- Barn door tailgate, tailgate skin made from 1/8"
 AR 450 HARDOX plate
- 25,000 lb. axles, 102" wide, outboard cast drums, steel hubs
- Watson & Chalin T.A. 300 Air Ride (30,000 lb. rated)
- 8' Minimizer Tanker Fenders to cover both axles
- Air controlled A.B.S. brake system (no electronics)
- 280", inverted, 5 stage hoist by HYVA Corp.
- Automatic airbag dump system with rear axle dump stands

- Air lift rear axle controlled with air switch on trailer forward of left front axle
- Manual landing gear mounted under draft arms
- Approved DOT lighting
- Air controlled sliding tandem unit
- · Hazardous latch on bottom center of tailgate
- Liquid filled air gauge on 5th wheel plate to monitor air in airbags (to monitor trailer weight)

Auto Tarps

- Shurco Auto Tarps
- Thick, Vinyl Coated Tarp
- Driver can automatically tarp the load from within the truck cab
- Auto tarps provide an additional level of safety.
 Drivers do not need to climb on equipment to tarp the load for hauling.

